ISSN: 3144-1920

Wissen PUBLICATION GROUP

Journal of
Environmental Sustainability and Renewable Systems

Review Article

Volume: 1 | Isssue: 1 | June 2026 | Pages 01–09

Review of Harmful Effects of Colloidal Silica after End Use Application in Environment

Agni Mohapatra

Indian Institute of Technology, Delhi, India

*Corresponding Author: Agni Mohapatra, Indian Institute of Technology, Delhi, India.


Submitted: 03 June 2026 **Accepted:** 11 June 2026 **Published:** 17 June 2026

Citation: Mohapatra, A. (2026). Review of Harmful Effects of Colloidal Silica after End Use Application in Environment. Journal of Environmental Sustainability and Renewable Systems, 1(1), 1-9. DOI: doi.org/10.67927/JEnvironSustainRenewSyst/2026(1)105.

Abstract

Colloidal silica is a technologically important inorganic nanomaterial extensively used in coatings, catalysts, polishing agents, paper processing, construction materials, biomedical systems, and numerous advanced industrial formulations owing to its high surface area, chemical stability, tunable particle size, and versatile surface chemistry. Although generally regarded as a low-toxicity and environmentally acceptable material, its increasing production and widespread discharge have prompted growing interest in its environmental fate and long-term impacts. Unlike bulk silica, colloidal silica remains highly dispersed in aqueous systems due to its small particle size and electrostatic stability, enabling prolonged transport and interaction with natural matrices. This review examines the behavior of colloidal silica in water, soil, sediment, and wastewater environments, highlighting how its physicochemical properties influence turbidity, light penetration, nutrient mobility, soil pore blockage, sediment modification, sludge generation, and treatment inefficiencies. Particular attention is given to indirect ecological effects on aquatic productivity, benthic habitats, microbial processes, and soil functionality, as well as occupational concerns associated with airborne dried residues and concentrated suspensions. Current mitigation strategies including coagulation–flocculation, membrane separation, process optimization, recovery and reuse, controlled discharge, and safe handling practices are also critically discussed. Overall, the environmental risks associated with colloidal silica arise less from acute toxicity and more from persistence, accumulation, and system-level physical interactions. A balanced understanding of these mechanisms is essential for developing sustainable management approaches that preserve the industrial advantages of colloidal silica while minimizing ecological and human health concerns.

Keywords: Colloidal Silica, Environment, Inorganic Nanomaterial, Water Pollution, Soil Pollution, Wastewater Treatment.



Introduction

Colloidal silica is one of the most widely utilized inorganic nanomaterials in modern industry, valued for its chemical stability, high surface area, tunable particle size, optical transparency, and versatile surface chemistry [1-3]. It is extensively employed in coatings, catalysts, polishing slurries, adhesives, paper processing, construction materials, pharmaceuticals, biotechnology, and advanced nanotechnology applications [4,5]. Because silica is naturally abundant and generally regarded as a low-toxicity material, colloidal silica has often been considered environmentally benign compared with many synthetic chemicals. However, the increasing scale of its production, widespread industrial use, and growing discharge through wastewater streams, manufacturing residues, and product life cycles have raised important questions regarding its environmental fate, transport, and long-term ecological impact [6,7]. Unlike bulk silica, colloidal silica exists as highly dispersed fine particles whose small size, strong surface charge,

and suspension stability allow it to persist in water, interact dynamically with soils and sediments, and challenge conventional treatment processes [8,9]. These physicochemical properties can influence turbidity, wastewater sludge generation, nutrient mobility, soil permeability, sediment structure, and biological habitats, even when direct chemical toxicity remains low. In addition, occupational exposure to dried airborne residues or concentrated suspensions highlights the need to evaluate human health considerations alongside environmental concerns. Despite its extensive commercial relevance, discussions on colloidal silica often focus primarily on synthesis and application, while its environmental behavior and management strategies receive comparatively less integrated attention. Therefore, this review aims to critically examine the interactions of colloidal silica with water, soil, sediment, wastewater systems, and biological environments, with particular emphasis on the mechanisms governing persistence, transport, accumulation, and indirect ecological effects. Furthermore, mitigation approaches, treatment technologies, safe handling practices, and future directions for sustainable use are discussed to provide a comprehensive perspective on balancing the technological benefits of colloidal silica with responsible environmental stewardship.

Harmful Effects of Colloidal Silica in Environment

Exposing colloidal silica to the environment can have varying impacts depending on the form, concentration, and exposure conditions. Potential harms of colloidal silica exposure in the environment are mainly associated with its persistence, fine particulate nature, and interactions with natural systems when released in excessive amounts [10]. In aquatic ecosystems, colloidal silica may alter the pH of water under high concentrations, which can disturb sensitive aquatic organisms and microbial communities [11]. Suspended silica particles can also increase water turbidity, reduce light penetration and thereby limiting photosynthesis of aquatic plants and algae [12]. Over time, the accumulation of silica-rich sediments may affect benthic organisms that live on or within the sediment layer. In soil environments, excessive colloidal silica can clog soil pores, decreasing aeration and restricting water infiltration, which may negatively influence root growth and soil microbial activity [13]. It may also react with naturally occurring minerals, potentially changing the physical structure or chemical balance of the soil. From a human health perspective, dried colloidal silica residues can become airborne as fine dust, creating inhalation risks that may lead to respiratory irritation [14]. Direct exposure to concentrated dispersions may additionally cause irritation to the skin and eyes. In wastewater systems, colloidal silica presents treatment challenges because it is not readily removed by conventional filtration or settling methods, increasing the likelihood of long-term release into water bodies [15]. Furthermore, its presence can contribute to sludge formation, placing additional operational burdens on wastewater treatment facilities. Most environmental protection agencies regulate the release of industrial and chemical waste, including colloidal silica. Excessive discharge into water bodies or landfills may require permits or adherence to specific guidelines [16].

To minimize the environmental footprint of colloidal silica, responsible handling and disposal practices are essential. Wherever possible, colloidal silica should be recovered and reused from industrial streams through established separation techniques such as coagulation, controlled precipitation, membrane filtration, or centrifugation [17]. These approaches not only reduce waste generation but also improve process sustainability and resource efficiency. If the dispersion has become chemically contaminated or its pH has shifted outside acceptable limits, it should be properly neutralized or conditioned before any discharge, ensuring compatibility with environmental standards and downstream treatment systems. Waste colloidal silica that cannot be recycled should be directed to authorized chemical or industrial waste management facilities where it can be treated safely. In cases involving only very small laboratory-scale quantities, careful dilution may sometimes be acceptable prior to disposal, but only when permitted under local environmental regulations and institutional safety guidelines.

Overall, colloidal silica is generally regarded as a low-hazard material when used in controlled amounts and managed appropriately. However, large-scale release, poor containment, or improper disposal can create operational and environmental concerns, particularly in water and soil systems. With thoughtful process control, recovery strategies, and regulatory compliance, colloidal silica can be handled in a manner that is both technically sound and environmentally responsible.




Figure 1: Overview of how Colloidal Silica Nanoparticles are Impacting Environment.

Impact on Aquatic Ecosystems

How it Impacts the pH of Aquatics

Although colloidal silica is generally regarded as chemically inert under most environmental conditions, its release into aquatic systems in significant quantities can still influence water chemistry, particularly pH, through a combination of dissolution, surface reactivity, and interactions with naturally occurring ions [18,19]. When dispersed silica particles remain suspended in water, a slow dissolution process may occur at the particle–water interface, producing dissolved monosilicic acid (H_4SiO_4). Because silicic acid is a weak acid, limited dissociation can release hydrogen ions into the surrounding medium, leading to a slight decrease in pH, especially in poorly buffered waters. The magnitude of this effect depends strongly on silica concentration, particle size, residence time, temperature, and the original alkalinity of the receiving water body [20]. In addition to dissolution, colloidal silica surfaces are rich in silanol (Si–OH) functional groups, which are amphoteric in nature and can either donate or accept protons depending on the ambient pH. Under acidic conditions, these surface groups may undergo proton exchange reactions that further contribute to acidity, whereas under alkaline conditions they may consume hydroxide ions or alter local buffering behavior [21]. Such interfacial chemistry becomes more pronounced for nanoscale or highly dispersed silica due to the larger specific surface area available for reaction.

Another important consideration is the interaction of colloidal silica with natural buffering systems such as bicarbonate, carbonate, calcium, and magnesium ions present in freshwater and marine environments [22,23]. By adsorbing ions or shifting equilibrium reactions at the particle surface, silica suspensions can subtly disturb the acid–base balance over time [24]. Commercial colloidal silica formulations may also contain stabilizing counterions such as sodium or ammonium species, introduced during manufacturing to maintain suspension stability [25]. These residual additives can sometimes have a greater immediate effect on pH than the silica particles themselves; sodium-stabilized systems may increase alkalinity, whereas ammonium-containing systems can contribute mild acidification through ammonium hydrolysis. At low environmental concentrations, these changes are typically negligible. However, localized high-load discharges, accidental spills, or chronic accumulation in poorly circulated waters may produce measurable pH deviations capable of stressing aquatic organisms. Even modest pH shifts can influence fish respiration, microbial metabolism, algal productivity, and reproductive cycles, while also altering the solubility, mobility, and toxicity of metals and nutrients already present in the ecosystem [26].

For these reasons, management of colloidal silica-containing effluents should extend beyond simple solids control and include water chemistry monitoring. Industrial or laboratory wastewater streams should ideally be conditioned to near-neutral pH before release, and where necessary, dilution or buffering treatments may be employed to minimize localized excursions in acidity or alkalinity. Recovery of silica solids prior to discharge through coagulation, membrane separation, or sedimentation further reduces both particulate loading and downstream chemical impacts. Thus, while colloidal silica is not intrinsically a highly hazardous material, its environmental behavior is governed by concentration, formulation, and receiving-water chemistry, making responsible process control essential for sustainable use.

Influence of the Turbidity of Water Bodies

Suspended colloidal silica particles can substantially increase the turbidity of water, thereby reducing clarity and limiting the penetration of sunlight that sustains aquatic life [27,28]. Because colloidal silica exists as extremely fine particles—often in the nanometer to submicron range—it does not settle rapidly like coarse sand or silt. Instead, these particles remain dispersed for extended periods due to their small size and electrostatic surface charge, which causes mutual repulsion and prevents aggregation. This stable suspension scatters incoming light in multiple directions and, to a lesser extent, absorbs portions of the light spectrum, giving the water a cloudy or milky appearance. As turbidity rises, less solar radiation can penetrate to deeper layers of the water column, shrinking the photic zone where photosynthesis can occur. This has immediate ecological consequences because phytoplankton, algae, and submerged aquatic plants depend on sunlight as their primary energy source. When light availability declines, photosynthetic productivity decreases, resulting in lower biomass generation and reduced oxygen release into the surrounding water [29].

The ecological effects can extend far beyond reduced plant growth. Phytoplankton and aquatic vegetation form the foundation of many freshwater and marine food webs, supporting zooplankton, invertebrates, fish, and higher predators [30]. A sustained reduction in primary productivity can therefore cascade through the ecosystem, lowering food availability and altering species abundance. In shallow lakes, rivers, or wetlands, light deprivation may eliminate rooted submerged vegetation that normally stabilizes sediments, shelters juvenile organisms, and absorbs nutrients [31]. Once these plants decline, the habitat may shift toward a more degraded, turbid state dominated by species tolerant of low-light or disturbed conditions. Reduced photosynthesis can also contribute to lower dissolved oxygen levels, particularly at night or during warm weather, increasing stress on fish and other aerobic organisms. In severe cases, localized hypoxia may develop [32].

Secondary impacts are also important. Over time, suspended silica particles may gradually settle onto the sediment surface, where they can blanket benthic habitats and interfere with filter-feeding organisms, eggs, larvae, or bottom-dwelling invertebrates [33]. Elevated turbidity may also influence thermal behavior by changing how sunlight is absorbed and distributed in the water column, potentially affecting temperature-sensitive species and stratification patterns [34]. In real environmental settings, colloidal silica is rarely the sole stressor; when combined with nutrient-rich runoff or industrial wastewater, it may intensify broader water-quality problems such as eutrophication and oxygen depletion [35]. Accordingly, management of silica-containing effluents should prioritize turbidity control through coagulation–flocculation, membrane or granular filtration, settling tanks, and adherence to discharge standards for suspended solids [36]. Through such measures, the ecological risks associated with colloidal silica-induced turbidity can be substantially reduced while maintaining responsible industrial and laboratory practices.




Figure 2: Overview of Impact of Colloidal Silica in Water Pollution.

Bioaccumulation

Silica is widely regarded as a low-toxicity and naturally occurring material, present in rocks, soils, river systems, and even many biological structures. For this reason, silica itself is not typically considered chemically hazardous to aquatic organisms. However, environmental risk does not arise solely from chemical toxicity; it can also result from physical accumulation and habitat modification. When colloidal silica enters water bodies through industrial effluents, laboratory waste streams, or disturbed sediments, the fine suspended particles may gradually settle and become incorporated into bottom sediments. Over time, excessive deposition can create localized conditions that negatively affect benthic organisms—those worms, mollusks, crustaceans, insect larvae, and microorganisms that inhabit the sediment surface or live within the substrate [37]. These

communities are ecologically important because they recycle nutrients, decompose organic matter, oxygenate sediments through burrowing, and serve as a major food source for fish and birds.

One of the most immediate concerns is physical smothering of the sediment surface. Fine silica particles can form a blanket-like layer that covers natural substrates and restricts the normal exchange of oxygen, nutrients, and metabolic wastes between pore water in the sediment and the overlying water column [38]. Many benthic species depend on this exchange for respiration and feeding. Burrowing organisms may find it harder to move through compacted deposits, while filter feeders and surface grazers may lose access to suitable feeding zones. If the deposited layer becomes dense or cohesive, it can alter the natural texture of sediments, transforming sandy or organically rich bottoms into a more compact and less permeable material [39]. Because many benthic species are highly adapted to specific grain sizes and sediment structures, such changes can reduce habitat suitability, interfere with egg laying, and impair recruitment of juvenile organisms [40].

The accumulation of silica-rich fines may also disturb sediment biogeochemistry. Reduced permeability limits the diffusion of dissolved oxygen into deeper sediment layers, encouraging the development of oxygen-poor or anaerobic zones [41]. Under such conditions, microbial pathways shift, sometimes generating reduced compounds such as hydrogen sulfide or methane that are harmful to many aquatic organisms [42,43]. At the same time, essential microbial processes involved in nitrogen cycling—such as nitrification and denitrification—can be suppressed, leading to broader ecosystem imbalances in nutrient availability. Another indirect consequence is the burial of organic detritus and biofilms that many benthic animals rely upon as food. If organic matter becomes inaccessible beneath silica deposits, populations of detritivores may decline, with cascading effects on predators higher in the food web [44].

Although silica itself is relatively inert, its high surface area can also enable adsorption of trace contaminants already present in the environment, including metals or hydrophobic organic pollutants [45]. These contaminants may then become concentrated within sediments and enter food webs when ingested by benthic feeders, creating a pathway for long-term ecological exposure [46]. Such effects are most likely to occur near industrial discharge zones, dredging sites, or poorly managed wastewater outlets where repeated inputs of suspended silica occur [47]. Consequently, responsible management should focus on preventing excessive sediment loading through coagulation, clarification, filtration, and controlled discharge practices, coupled with periodic sediment monitoring in vulnerable areas [48]. In summary, while silica is not inherently poisonous, its persistent accumulation in sediments can indirectly harm benthic ecosystems through smothering, habitat alteration, oxygen depletion, and disruption of ecological processes, underscoring the importance of proper environmental stewardship.

Interaction with Soil

Clogging of Soil Pores

Colloidal silica, although chemically stable and often regarded as low hazard, can create significant physical impacts in soil when introduced repeatedly or in high concentrations through irrigation water, industrial wastewater reuse, or land disposal practices [49]. Because colloidal silica consists of extremely fine particles—commonly in the nanometer to submicron range—it behaves differently from coarse mineral matter. These particles remain suspended in water for long periods and are easily transported into the soil profile during infiltration [50]. Their small size allows them to enter micropores and narrow flow channels that are essential for air exchange, water movement, and root-zone functioning. Once inside the soil matrix, changes in water velocity, drying cycles, ionic strength, or contact with clay minerals and dissolved salts can destabilize the suspension, causing the particles to deposit or aggregate within pore spaces. Over time, repeated inputs may gradually seal pores or form thin silica-rich coatings along soil particles, reducing the openness and connectivity of the pore network.

The blockage of soil pores has direct consequences for soil aeration. Healthy soils contain a balance of solid particles, water-filled pores, and air-filled pores. These air-filled spaces allow oxygen to diffuse downward to plant roots and soil microorganisms while permitting carbon dioxide and other gases to escape. When fine silica accumulates and obstructs these pathways, oxygen transfer slows and the root zone may become poorly aerated. Plant roots under oxygen stress often exhibit reduced respiration, slower nutrient uptake, and weakened growth. Beneficial aerobic microorganisms that drive decomposition and nutrient mineralization may also decline, while anaerobic microbial populations become more dominant. Under prolonged oxygen-limited conditions, undesirable by-products such as methane, organic acids, or hydrogen sulfide may form, further degrading soil quality and plant health [51].

Water infiltration is similarly affected. Soil permeability depends on interconnected pores that allow rainwater or irrigation water to move downward and be stored for later plant use. When colloidal silica narrows or blocks these pathways, infiltration rates decrease, causing water to pond at the surface or move laterally as runoff [52]. This not only wastes irrigation water but also increases erosion risk and nutrient loss from the topsoil. In heavier or naturally poorly drained soils, silica-induced pore clogging can intensify waterlogging, leading to root damage, compaction, and reduced crop productivity [53,54]. Repeated wetting and drying may then harden the affected layers, creating crusts or dense zones that are difficult for roots to penetrate.

Interactions with existing soil components can amplify these effects. Colloidal silica may bind with clays, iron oxides, calcium salts, or organic matter, changing aggregate stability and modifying the natural structure of the soil [55]. In some cases, this may produce a denser, less friable soil with reduced tilth and poorer seedling emergence. Such impacts are most relevant in systems where silica-bearing waters are used continuously, such as reclaimed wastewater irrigation, industrial water reuse, or natural waters rich in suspended siliceous fines. Effective management therefore requires preventive treatment of water sources through coagulation, filtration, or settling, combined with periodic monitoring of irrigation water quality and soil hydraulic performance. Organic amendments, gypsum, deep ripping, or flushing with clean water may help restore pore continuity where buildup has occurred [56]. In summary, while colloidal silica is not inherently toxic, its persistent accumulation can impair the physical functioning of soils by restricting aeration, slowing infiltration, and reducing long-term soil productivity.




Figure 3: Overview of Soil Pollution by Accumulation of Colloidal Silica in Soil.

Colloidal Silica Threats Chemical Reactions in Soil

Colloidal silica can interact with soil minerals through a complex combination of physical deposition, surface adsorption, ion exchange, and electrochemical processes, and these interactions may gradually modify both the physical structure and chemical behavior of soils [57]. Because colloidal silica particles possess a high specific surface area and are commonly covered with silanol (Si–OH) groups, they usually carry a net negative charge under natural soil pH conditions. This surface charge makes them highly reactive toward positively charged mineral surfaces and dissolved cations present in soil pore water [58]. In acidic soils, minerals such as iron and aluminum oxides often contain protonated surface sites with positive charge, allowing colloidal silica to adsorb strongly onto them. Clay minerals, organic colloids, and metal hydroxides may also serve as attachment points. As these particles accumulate on mineral surfaces, they can alter the charge balance, surface reactivity, and cation exchange behavior of the soil, thereby influencing how nutrients and contaminants are retained or released.

One important consequence of these interactions is the effect on nutrient availability. Colloidal silica can adsorb or associate with essential plant nutrients such as potassium, calcium, magnesium, ammonium, and phosphate, reducing their immediate mobility in the soil solution. In some situations, this may help slow nutrient leaching and provide a buffering reservoir; however, excessive silica loading can immobilize nutrients to the point that plant roots experience reduced access [59]. Phosphate is particularly sensitive because it strongly interacts with oxide surfaces already coated or modified by silica, potentially shifting phosphorus sorption dynamics. In addition, dissolved silicic acid formed from partial silica dissolution may compete with phosphate or other oxyanions for reactive sorption sites. These subtle changes can influence fertilizer efficiency, root uptake patterns, and long-term soil fertility [60,61].

Colloidal silica can also reshape soil structure. Depending on the ionic composition of the soil solution, especially the presence of calcium, sodium, or salts, silica particles may either stabilize dispersion or promote flocculation of fine clays [62]. Moderate aggregation may improve crumb structure, pore continuity, and aeration. However, if deposition becomes excessive, silica can cement particles together or form dense micro-aggregates that reduce friability and root penetration [63,64]. Under alkaline or saline conditions, colloidal silica may condense into gel-like networks that bind particles into semi-impermeable layers. Such layers can restrict infiltration, slow drainage, and create perched water zones or hardpan-like horizons. This is particularly relevant in irrigated soils receiving silica-rich water over long periods [65].

The chemistry of the soil solution may also shift. Although silica is only weakly acidic, dissolved silicic acid can contribute small pH changes, especially in poorly buffered soils. More importantly, silica interactions can indirectly influence pH by modifying the solubility of calcium carbonates, iron oxides, aluminum species, and phosphate minerals [66]. Colloidal silica may also react with cations such as calcium, iron, or magnesium to form secondary silicate precipitates, changing mineral equilibria and immobilizing nutrients. These processes may be slow, but over seasons or years they can measurably affect soil behavior.

Soil microbial communities are not immune to these changes. Fine silica coatings on mineral particles or microbial biofilms may alter habitat surfaces, water films, and nutrient accessibility. If aeration declines or nutrients become less available, microbial activity linked to decomposition, nitrogen cycling, and organic matter turnover may also decline. Conversely, in some soils improved aggregation may create more stable microbial niches. Thus, the impact of colloidal silica is highly context dependent. In agricultural lands, industrial discharge zones, or land-reclamation systems, careful monitoring of irrigation water quality, soil structure, drainage, and nutrient balance is advisable. Organic amendments, gypsum, lime, and sound fertility management can often offset undesirable effects. Overall, colloidal silica is not inherently harmful to soils, but excessive accumulation or mismanaged inputs can alter mineral interactions in ways that reduce productivity and soil ecological function over time.

Impact on Human Health

Respiratory Risks

Although colloidal silica is often regarded as a relatively low-toxicity material in its liquid dispersion form, occupational and environmental concerns can arise when the product dries and leaves behind fine particulate residues. Once the liquid phase evaporates, extremely small silica particles remain as a powder that can be easily disturbed during handling, sweeping, packaging, or equipment cleaning. Because these particles may range from nanometer to micrometer scale, they can become suspended in air for extended periods and behave as respirable dust. When inhaled, the finest fractions are capable of penetrating deep into the respiratory tract and reaching the bronchioles or alveolar regions of the lungs. Short-term exposure may cause irritation of the nose, throat, and upper airways, leading to coughing, dryness, discomfort, or transient shortness of breath. Individuals with pre-existing respiratory conditions such as asthma, bronchitis, or heightened dust sensitivity may experience stronger symptoms even at comparatively lower exposure levels.

The long-term health significance depends strongly on the form of silica present. Crystalline silica, such as quartz dust, is well established as a serious occupational hazard associated with silicosis, chronic lung disease, and increased cancer risk. Colloidal silica products, however, are generally composed of amorphous silica, which is substantially less biologically aggressive than crystalline forms. Even so, repeated inhalation of high concentrations of amorphous silica dust over long durations can still burden the lungs, provoke chronic irritation, and in some cases contribute to inflammatory or fibrotic changes. For this reason, industries involved in coatings, polishing, ceramics, catalysts, paper treatment, or advanced materials where

dried silica residues may be generated should not assume the material is risk free simply because it is non-crystalline. Proper ventilation, dust capture systems, enclosed handling, and air monitoring remain important preventive measures. Wet cleaning methods or HEPA-filter vacuuming are preferred over dry sweeping, which readily re-aerosolizes settled dust. Where airborne exposure is possible, appropriate respiratory protection such as well-fitted particulate masks or respirators may be necessary in accordance with workplace standards.

Direct contact with concentrated colloidal silica dispersions can also irritate the skin and eyes, primarily through physical rather than severe chemical toxicity. Many commercial colloidal silica suspensions are mildly alkaline, often maintained at elevated pH to keep particles stable and prevent aggregation. Repeated skin contact with such alkaline dispersions may disrupt the natural lipid barrier of the skin, causing dryness, redness, itching, or mild burning sensations. In addition, the fine suspended particles can create a slight abrasive effect, especially when rubbed onto already sensitive or damaged skin. People with dermatitis, eczema, or frequent hand washing may be more susceptible because their protective skin barrier is already compromised. Wearing chemical-resistant gloves, protective clothing, and minimizing direct contact are therefore sensible precautions during routine handling.

The eyes are particularly sensitive because even minor particulate exposure can cause significant discomfort. Splashing of concentrated colloidal silica or transfer of residues from contaminated hands may deposit particles onto the conjunctiva or corneal surface, producing a gritty sensation, tearing, redness, and irritation. The mild alkalinity of the suspension may intensify this discomfort by disturbing the natural pH of the tear film. If particles remain trapped or the eyes are rubbed, superficial abrasions or inflammation may occur. Immediate flushing with clean lukewarm water for at least fifteen minutes is the standard first response, followed by medical attention if pain, redness, or blurred vision persists. Safety goggles or face shields are especially important where splashing, spraying, or pressurized transfer operations occur.

Overall, colloidal silica is not among the most hazardous industrial materials, but its safe use depends on understanding how form and exposure route change risk. As a stable liquid dispersion it is generally manageable, whereas dried airborne residues can present inhalation hazards and concentrated suspensions may irritate skin and eyes. Good housekeeping, ventilation, personal protective equipment, training, and prompt first-aid measures are usually sufficient to control these risks and ensure safe handling in laboratories and industrial settings.




Figure 4: Overview of Impact of Colloidal Silica on Human Health.

Wastewater Issues

Difficulty in Treatment

Colloidal silica presents a distinctive challenge in wastewater treatment because it behaves very differently from ordinary suspended solids such as silt, sand, or organic debris. Although silica itself is a naturally occurring and generally low-toxicity material, its colloidal form consists of extremely fine particles often in the nanometer range—that remain stably dispersed in water for long periods. These particles are so small that gravity has little influence on them, and they do not readily settle to the bottom like larger solids. In addition, their surfaces usually carry a negative electrical charge, creating repulsive forces between neighbouring particles. This electrostatic stability prevents them from clumping together naturally, allowing the suspension to remain clear to the eye while still containing a substantial load of dispersed silica. As a result, wastewater containing colloidal silica may appear manageable while still being difficult to treat through conventional means.

Traditional treatment systems often rely on coagulation, flocculation, sedimentation, and filtration. These methods are highly effective for many common contaminants, yet colloidal silica frequently resists each step. Standard coagulants such as alum or ferric salts are designed to neutralize particle charges and promote the formation of larger flocs that can settle. However, colloidal silica has a high surface area and strong surface charge, so typical dosing conditions may not fully destabilize the particles. Even when some aggregation occurs, the resulting flocs are often small, light, and slow-settling. This limits the performance of clarifiers and sedimentation tanks, which depend on gravity separation. In practical terms, operators may find that treated water still carries residual turbidity or silica despite apparently normal treatment conditions.

Filtration can be equally problematic. Conventional sand filters or cartridge filters are generally designed to capture larger particulates and may allow colloidal silica to pass through because the particles are far smaller than the effective pore spaces. More advanced technologies such as ultrafiltration, nanofiltration, or reverse osmosis can remove colloidal silica more effectively, but these systems are significantly more expensive to install and operate. They also face membrane fouling, where silica deposits accumulate on surfaces, reducing flow rates and increasing maintenance demands. In industrial water reuse systems, colloidal silica is especially troublesome because it can scale membranes, heat exchangers, and piping while also reducing the efficiency of purification units.

If not adequately removed, colloidal silica may persist in discharged effluents and gradually accumulate in receiving water bodies, especially where repeated industrial discharge or runoff occurs. While silica is not inherently poisonous, long-term loading can still create environmental stress. Elevated concentrations may increase turbidity, reduce light penetration, and interfere with photosynthesis by algae and submerged plants. Settled deposits may also alter sediment texture and aquatic habitats over time. Because the issue is often physical rather than acutely toxic, it may receive less immediate attention than conventional pollutants, yet chronic accumulation can still degrade water quality and ecosystem function.

For this reason, effective management of colloidal silica often requires a more tailored treatment strategy than standard waste-

water processes alone. Optimized pH control, specialty polymer coagulants, electrocoagulation, dissolved air flotation, or membrane-based polishing steps may be needed depending on the source stream. Increasingly, industries are also exploring silica recovery and reuse rather than simple disposal, which can reduce both treatment burden and raw material waste. In essence, colloidal silica reminds engineers that not all contaminants are harmful because of toxicity—some are challenging because of how persistently and invisibly they behave in water. With proper process design, monitoring, and modern treatment technologies, these challenges can be managed responsibly and efficiently.




Figure 5: Overview of Difficulty in Wastewater Treatment.

Sludge Production

Colloidal silica can significantly contribute to sludge formation in wastewater treatment systems, creating added operational and economic pressure for treatment plants. Although silica itself is not highly toxic, its colloidal form behaves as a persistent fine particulate material with a very high surface area and reactive surface chemistry. These properties allow silica particles to adsorb dissolved organic matter, metal ions, oils, and other suspended contaminants commonly present in wastewater. As treatment proceeds, these adsorbed materials become incorporated into aggregates or flocs, which eventually settle out as sludge. In this way, colloidal silica often acts as a binding scaffold that captures additional solids, increasing the total mass of sludge generated beyond what would occur from wastewater contaminants alone.

During coagulation and flocculation processes, the presence of colloidal silica can further complicate solids separation. Standard treatment chemicals such as alum, ferric chloride, or polymeric flocculants are added to destabilize suspended particles and form settleable flocs. However, colloidal silica is highly stable in water and may require greater chemical dosages to neutralize its surface charge and encourage aggregation. The resulting flocs can become denser or more voluminous, contributing to larger sludge yields. This not only raises chemical consumption but also increases the quantity of solids that must be thickened, dewatered, transported, and ultimately disposed of. For wastewater plants operating near capacity, even moderate increases in sludge production can strain existing infrastructure.

Another challenge lies in the physical nature of silica-rich sludge. Because silica surfaces are strongly hydrophilic, they tend to retain water within the sludge matrix, often producing a gel-like or sticky consistency. Such sludge can be more difficult to thicken and dewater efficiently, requiring additional polymer conditioning, longer residence times, or higher energy input for centrifuges, belt presses, or thermal drying systems. Higher moisture content also increases transport and disposal costs because more mass is being moved with less actual solids content. In some cases, the fine and mildly abrasive character of silica particles can accelerate wear on pumps, pipelines, centrifuge bowls, and other mechanical handling equipment, increasing maintenance frequency and replacement costs.

Disposal of silica-laden sludge may also become more complicated depending on its composition. If the sludge contains adsorbed metals, organics, or other regulated contaminants, beneficial reuse options such as land application may be limited. Incineration or landfill disposal then becomes more likely, both of which carry additional cost and environmental burden. For industrial facilities with high silica wastewater streams, sludge management can therefore become one of the most expensive downstream consequences of poor silica control.

To reduce these impacts, treatment plants often benefit from addressing colloidal silica earlier in the process rather than relying solely on conventional sludge handling. Optimized coagulation chemistry, pH adjustment, specialty flocculants, dissolved air flotation, membrane pretreatment, or electrocoagulation may improve silica capture before it enters the main treatment train. Advanced dewatering systems and selective recovery methods may also help convert silica-rich sludge into reusable by-products in some industries. In essence, colloidal silica is not problematic because of toxicity alone, but because it quietly increases sludge volume, water retention, chemical demand, and operational complexity. Effective management of silica at the source can therefore substantially improve the efficiency and sustainability of wastewater treatment systems.

Conclusion

In conclusion, colloidal silica is generally considered a low-toxicity and widely useful material, yet its environmental and operational impacts become significant when released or accumulated in unmanaged quantities. Owing to its extremely fine particle size, high surface area, and stable suspension behavior, it can persist in water, contribute to turbidity, interfere with wastewater treatment, increase sludge generation, and alter soil structure, nutrient balance, and aeration. In aquatic and sediment environments, excessive buildup may disrupt light penetration, benthic habitats, and broader ecological processes, while dried residues can pose inhalation and irritation risks during handling. These concerns are driven less by inherent chemical toxicity and more by the material's physical behavior and long-term persistence. Therefore, responsible use of colloidal silica requires appropriate recovery, containment, treatment, monitoring, and disposal practices so that its industrial benefits can be realized without compromising environmental quality or human safety.

References

1. Hyde, E.D.E.R., Seyfaee, A., Neville, F., Moreno-Atanasio, R. (2016). Colloidal silica particle synthesis and future industrial manufacturing pathways: A review. Industrial Engineering Chemistry Research, 55, 8891-8913.
2. Li, S., van der Ven, L.G.J., Spoelstra, A.B., Tuinier, R., Esteves, A.C.C. (2023). Tunable distribution of silica nanoparticles in water-borne coatings via strawberry supracolloidal dispersions. Journal of Colloid and Interface Science, 646, 185-197.
3. Huang, Y. (2022). Silica nanoparticles: Biomedical applications and toxicity. Biomedicine Pharmacotherapy, 151, 113053.

4. Calderón-Guillén, J.A., Avilés-Arellano, L.M., Pérez-Robles, J.F., González-Hernández, J., Ramos-Ramírez, E. (2005). Dense silica-based coatings prepared from colloidal silica. Surface Coatings Technology, 190, 110-114.
5. Dong, X., Wu, P., Hellmann, G.P., Wang, C., Schäfer, C.G. (2017). Morphology-controlled coating of colloidal particles with silica: Influence of particle surface functionalization. Langmuir, 33, 2235-2247.
6. Jarvie, H.P. (2009). Fate of silica nanoparticles in simulated primary wastewater treatment. Environmental Science Technology, 43, 8622-8628.
7. Mah, H., Chew, Y., Low, S., Wan, T., Lim, J. (2025). Silicon/silica colloidal waste in the semiconductor industry: Challenges in recovery and potential use. Langmuir, 41, 7151-7159.
8. Bakhshandeh, F., Noorzad, R., Ta'negonbadi, B. (2025). Experimental investigation of the properties of collapsible soil stabilized by colloidal silica. Scientific Reports, 15, 30032.
9. Wong, C., Pedrotti, M., El Mountassir, G., Lunn, R. J. (2018). A study on the mechanical interaction between soil and colloidal silica gel for ground improvement. Engineering Geology, 243, 84-100.
10. Book, F., Backhaus, T. (2022). Aquatic ecotoxicity of manufactured silica nanoparticles: A systematic review and meta-analysis. Science of the Total Environment, 806, 150893.
11. Nalumenya, B. (2024). Assessing the potential impacts of contaminants on the water quality of Lake Victoria: Two case studies in Uganda. Sustainability, 16.
12. Lan, J., Liu, P., Hu, X., Zhu, S. (2024). Harmful algal blooms in eutrophic marine environments: Causes, monitoring, and treatment. Water, 16.
13. Ghadir, P., Pedrotti, M. (2025). Nanoporous synthetic roots: Effect of drying paths on colloidal silica-plants interaction. E3S Web of Conferences, 642, 06010.
14. Cleveland Clinic. (n.d.). What is silicosis? Retrieved from https://my.clevelandclinic.org/health/diseases/22622-silicosis
15. Teng, W. (2023). Reliability treatment of silicon in oilfield wastewater by electrocoagulation. Water, 15.
16. Ahmed, M. (2022). Recent developments in hazardous pollutants removal from wastewater and water reuse within a circular economy. NPJ Clean Water, 5, 12.
17. Chuang, S. H., Chang, T. C., Ouyang, C. F., Leu, J. M. (2007). Colloidal silica removal in coagulation processes for wastewater reuse in a high-tech industrial park. Water Science Technology, 55, 187-195.
18. Taleb, M. A. (2024). Recent advances in heavy metals uptake by tailored silica-based adsorbents. Science of the Total Environment, 955, 177093.
19. Nthunya, L. N. (2025). Unseen threats in aquatic and terrestrial ecosystems: Nanoparticle persistence, transport and toxicity in natural environments. Chemosphere, 382, 144470.
20. Wong, C., Pedrotti, M., El Mountassir, G., Lunn, R. J. (2018). A study on the mechanical interaction between soil and colloidal silica gel for ground improvement. Engineering Geology, 243, 84-100.
21. Lindgård, J. (2012). Alkali-silica reactions (ASR): Literature review on parameters influencing laboratory performance testing. Cement and Concrete Research, 42, 223-243.
22. Karami, A. (2009). Study on modification of colloidal silica surface with magnesium ions. Journal of Colloid and Interface Science, 331, 379-383.
23. Iler, R. K. (1975). Coagulation of colloidal silica by calcium ions, mechanism, and effect of particle size. Journal of Colloid and Interface Science, 53, 476-488.
24. Gorrepati, E. A., Wongthahan, P., Raha, S., Fogler, H. S. (2010). Silica precipitation in acidic solutions: Mechanism, pH effect, and salt effect. Langmuir, 26, 10467-10474.
25. Pan, M.-C. (2007). Effect of variant counterions on stability and particle size of silica sol. Chinese Journal of Chemistry, 25, 1514-1521.
26. Beil, S. (2021). Toward the proactive design of sustainable chemicals: Ionic liquids as a prime example. Chemical Reviews, 121, 13132-13173.
27. Kinyua, E. M., Mwangi, I. W., Wanjau, R. N., Ngila, J. C. (2016). Clarification of colloidal and suspended material in water using triethanolamine modified maize tassels. Environmental Science and Pollution Research, 23, 5214-5221.
28. Bao, X., Jin, Z., Cui, H., Chen, X., Xie, X. (2019). Soil liquefaction mitigation in geotechnical engineering: An overview of recently developed methods. Soil Dynamics and Earthquake Engineering, 120, 273-291.
29. Bashir, I. (2020). Concerns and threats of contamination on aquatic ecosystems. Bioremediation Biotechnology, 1-26.
30. Wu, J. (2025). Nutritional quality of phytoplankton shapes estuarine food webs under salinity and nutrient stress. ACS ES&T Water, 5, 3066-3077.
31. Zhang, Y. (2016). Aquatic vegetation in response to increased eutrophication and degraded light climate in Eastern Lake Taihu. Scientific Reports, 6, 23867.
32. Zhang, F. (2025). Dissolved oxygen dynamics in a shallow eutrophic lake: Quantify critical eco-environmental effects. Ecological Indicators, 179, 114190.
33. Wilber, D. H., Clarke, D. G. (2001). Biological effects of suspended sediments. North American Journal of Fisheries Management, 21, 855-875.
34. Birmachu, A. B., Feyissa, T. A., Tukura, N. G. (2024). Effects of turbidity variation on water temperature and evaporation. Journal of Engineering, 8891990.
35. Ejiohuo, O. (2025). Ensuring water purity: Mitigating environmental risks and safeguarding human health. Water Biology Security, 4, 100341.
36. Djouider, F., Banoqitah, E., Alhawsawi, A. (2024). Silica removal in water by electro-Fenton method. Desalination and Water Treatment, 317, 100118.
37. Book, F. (2022). Colloidal silica nanomaterials reduce pesticide toxicity to algae. Environmental Science: Nano, 9, 2402-2416.
38. Loder, T. C. (1978). Silicate in anoxic pore waters and oxidation effects during sampling. Nature, 273, 373-374.
39. Lundquist, C. J. (2018). Changes in benthic community structure after seagrass recolonisation. Scientific Reports, 8, 13250.
40. Weinert, M. (2022). Benthic ecosystem functioning under climate change. PeerJ, 10, e14105.
41. Michalopoulos, P. (2025). Microbial activity enhances silica cycling rates in marine sediments. Communications Earth Environment, 6, 982.
42. Zinder, S. H., Brock, T. D. (1978). Methane, carbon dioxide, and hydrogen sulfide production in sediments. Applied and Environmental Microbiology, 35, 344-352.
43. Sinkko, H. (2019). Oxygen deficiency changes bacterial communities in coastal sediments. Scientific Reports, 9, 16341.

44. Dias, E., Morais, P., Antunes, C., Hoffman, J. C. (2023). Benthic food web connects estuarine habitats. Food Webs, 35, e00282.
45. Samani, M. (2024). Nano silica-mediated stabilization of heavy metals in soils. Scientific Reports, 14, 20496.
46. Shao, Z.-D. (2025). Selective adsorption of ammonia using silica aerogel. Chemical Engineering Journal, 514, 163107.
47. Kubo, A., Kawarasaki, K., Hara, H. (2022). Silica removal at sewage treatment plants causes silica deficiency. Scientific Reports, 12, 8141.
48. Nahin, M. N. I. (2025). Respirable silica in ambient air and health risks. Scientific Reports, 15, 37309.
49. Wong, C. (2018). Mechanical interaction between soil and colloidal silica gel. Engineering Geology, 243, 84-100.
50. Wang, X., Xie, H., Wang, P., Yin, H. (2023). Nanoparticles in plants: Uptake and transport. Materials, 16, 3097.
51. Du, Y. (2023). Soil pore structure and greenhouse gas dynamics. Science of the Total Environment, 895, 165192.
52. Ju, X. (2024). Soil pore structure and infiltration characteristics. Soil Tillage Research, 236, 105922.
53. Zhang, Y. (2025). Soil waterlogging impacts and adaptive strategies. Frontiers in Plant Science, 16, 1545912.
54. Correa, J. (2019). Soil compaction and root system plasticity. Journal of Experimental Botany, 70, 6019-6034.
55. Zhang, L. (2025). Ion toxicity in waterlogged soils. Frontiers in Plant Science, 16, 1653008.
56. Meregildo Collave, C. X. (2024). Turbidity and color removal from irrigation water using Arduino system. Case Studies in Chemical and Environmental Engineering, 10, 100978.
57. Bakhshandeh, F. (2025). Experimental investigation of collapsible soil stabilized by colloidal silica. Scientific Reports, 15, 30032.
58. Ghojavand, S. (2023). Interplay between alkali-metal cations and silanol sites in zeolite. Communications Chemistry, 6, 134.
59. Greger, M., Landberg, T., Vaculík, M. (2018). Silicon influences nutrient availability in plants. Plants, 7, 41.
60. Sabur, M. A. (2022). Effects of pH and dissolved silicate on phosphate partitioning. ACS Earth and Space Chemistry, 6, 34-43.
61. Schaller, J. (2022). Silicon as a limiting factor for phosphorus availability in soils. Scientific Reports, 12, 16329.
62. Klotzbücher, T. (2020). Sorption competition controlling silicon mobility in soil. Scientific Reports, 10, 11225.
63. Marik, S. (2022). Silica-based additive for subgrade construction. Case Studies in Construction Materials, 17, e01229.
64. de Oliveira, J. A. T. (2022). Soil pore system complexity under management practices. Soil Tillage Research, 224, 105497.
65. Barbosa, L. A. P. (2024). Organic carbon and silica effects on soil stability. Scientific Reports, 14, 8330.
66. Limo, M. J. (2018). Metal oxide-biomolecule interactions. Chemical Reviews, 118, 11118-11193.

Copyright: *©2026 Agni Mohapatra. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.*